



BioMates

# PRODUCING SINGLE PHASE FAST PYROLYSIS CONDENSATES FROM STRAW BY STAGED CONDENSATION

Stefan Conrad<sup>1,2</sup>, Cristina Blajin<sup>1</sup>, T. Schulzke<sup>1</sup>

<sup>1</sup>Fraunhofer Institute for Environmental, Safety, and Energy Technology UMSICHT, Oberhausen, Germany |

<sup>2</sup>Ruhr-Universität Bochum, Faculty of Mechanical Engineering, Bochum, Germany

## ISSUE

Fast pyrolysis crude bio-oils from straw spontaneously decompose into two phases: a tarry-like phase at the bottom and an aqueous phase on top (Figure 1). In this phase separation process water content in the bio-oil plays a vital role. This investigation focuses on the influence of staged condensation temperature on the water content of the condensates, with the aim of finding the minimum temperature at which the resulting bio-oils collected in the 1<sup>st</sup> stage will have single phase.



Fig. 1: Two-phase total condensate (left) and single-phase staged condensate (right).

## METHODS

The experimental part was carried out in an ablative fast pyrolysis lab-scale reactor (550 °C pyrolysis temperature, 4.2 kg/h biomass and 4.9 kg/h nitrogen input) in combination with a two-stage condensation chain installed in a side-stream (internally cooled condenser and an electrostatic aerosol precipitator at each stage). The condensation temperature of the 1<sup>st</sup> stage was varied by changing the cooling medium temperature from 60 °C to 80 °C and the temperature of the cooling medium in the 2<sup>nd</sup> stage was kept constant at 4 °C.

## RESULTS

The total condensate (4 °C) had a calculated water content (19.6 wt.% tarry phase, 72.3 wt.% aqueous phase) of 48.6 wt.%. The bio-oil produced in the 1<sup>st</sup> fraction showed a phase separation above a critical water content, which lies between 25.1 wt.% and 35.9 wt.% at condensation temperature at and below 62.8 °C and no phase separation above 65.8 °C (Figure 2).




Fig. 2: Relationship between phase separation and water content of the whole 1<sup>st</sup> stage bio-oil depending on the condensation temperature.

The organics but also water in the 1<sup>st</sup> stage tarry phase increase at the transition between two-phase condensate (62.8 °C) and single-phase condensate (65.8 °C). With increased condensation temperature more and more water but also organics (including organic acids) will be lost to the 2<sup>nd</sup> stage (Figure 3).




Fig. 3: Distribution of water and organics on the tarry and aqueous phase from 1<sup>st</sup> and 2<sup>nd</sup> stage condensates.

The minimum vapour temperature at which the 1<sup>st</sup> stage condensates will be single-phase bio-oils was found to be 65.8 °C. At higher temperature, the water content and TAN decrease significantly at moderate loss of organics.

## CONTACT

\*Fraunhofer Institute for Environmental, Safety and Energy Technology UMSICHT

Osterfelder Strasse 3 | 46047 Oberhausen | Germany

Phone: +49 208 8598-0 | E-mail: biomates@biomates.eu

## PARTNERS

Imperial College London

Fraunhofer UMSICHT

ifeu INSTITUTE FOR ENERGY AND ENVIRONMENTAL RESEARCH HEIDELBERG

UNIVERSITY OF CHEMISTRY AND TECHNOLOGY PRAGUE



CERTH CENTRE FOR RESEARCH & TECHNOLOGY HELLAS



HyET Hydrogen Efficiency Technologies



biomates.eu



This project has received funding from the European Union's Horizon 2020 research and innovation programme under grant agreement No 727463. This poster reflects only the authors' view; the European Commission and its responsible executive agency INEA are not responsible for any use that may be made of the information it contains.